


## Robinets droits

Legris



### Spécifications techniques

Corps: laiton

Joint: PTFE

Bille: laiton nickelé et chromé dur

Température d'utilisation: -20°C à +150°C

| code     | dimensions (mm) |    |    |      |    |    |      |     |
|----------|-----------------|----|----|------|----|----|------|-----|
| commande | C               | DN | PN | E    | F  | H  | L    | M   |
| 237-8068 | 1/4 "           | 10 | 30 | 11   | 20 | 43 | 51,5 | 98  |
| 189-2737 | 3/8 "           | 10 | 30 | 11,4 | 20 | 43 | 51,5 | 98  |
| 189-2743 | 1/2 "           | 15 | 30 | 13,5 | 25 | 47 | 55   | 98  |
| 189-2759 | 3/4 "           | 20 | 30 | 12,5 | 31 | 58 | 57,5 | 122 |
| 189-2771 | 1"              | 25 | 30 | 15   | 38 | 60 | 69,5 | 122 |
| 189-2787 | 1 1/4 "         | 32 | 25 | 17   | 48 | 77 | 81,5 | 153 |
| 189-2793 | 1 1/2 "         | 40 | 25 | 18   | 54 | 83 | 95   | 153 |
| 189-2800 | 2"              | 50 | 25 | 22   | 66 | 95 | 113  | 162 |

U.D.V. = 1

| réf.       | code     | prix de l'U.D.V. |        |
|------------|----------|------------------|--------|
| Legris     | commande | 1-9              | 10+    |
| 4902 10 13 | 237-8068 | 27,90            | 25,81  |
| 4902 10 17 | 189-2737 | 27,90            | 25,81  |
| 4902 15 21 | 189-2743 | 31,98            | 29,58  |
| 4902 20 27 | 189-2759 | 43,21            | 39,97  |
| 4902 25 34 | 189-2771 | 61,15            | 56,56  |
| 4902 32 42 | 189-2787 | 88,76            | 82,10  |
| 4902 40 49 | 189-2793 | 111,27           | 102,92 |
| 4902 50 48 | 189-2800 | 135,43           | 125,27 |